

Silkolene®

V-Twin 20W-50

A dedicated high performance engine oil for V-Twin engines

Description

SILKOLENE V-TWIN 20W-50 is formulated on highly refined mineral base oils and performance additives.

SILKOLENE V-TWIN 20W-50 provides high levels of engine cleanliness and protects engine components from wear and corrosion.

Application

SILKOLENE V-TWIN 20W-50 is specifically formulated for use in Harley Davidson engines and other Metric V-Twin engines where a 20W-50 grade is specified.

Advantages

- Excellent wear, corrosion and oxidation protection
- Protects over a wide range of operating temperatures and conditions
- Promotes a high level of engine cleanliness
- Keep critical engine components operating at maximum efficiency

Specifications

- API SL
- JASO MA, MA2

Product Information



Further Information

Characteristics	Test Method	Unit	Results
SILKOLENE V-TWIN ...			20W/50
Colour	Visual		Dark amber
Specific Gravity at 15°C	IP160		0.891
Kinematic Viscosity @ 40°C	IP71	mm ² /s	168.4
Kinematic Viscosity @ 100°C	IP71	mm ² /s	19.1
Viscosity Index (VI)	IP226		129
Cold Crank Viscosity@ -15°C	ASTM D5293	cP	7900
Dynamic Viscosity @ -26°C	DIN 51398	cP	-
Flash Point	IP34	°C	
Pour point	IP15	°C	

Updated Dec 2019 ABUK

FUCHS LUBRICANTS (UK) plc
New Century Street, Hanley
Stoke-on-Trent, Staffordshire, ST1 5HU

Tel +44 (0)1782 203700
contact-uk@fuchs.com



Health, Safety and Environment - information is provided for products in the relevant Safety Data Sheet. This provides guidance on potential hazards, precautions and first-aid measures, together with environmental effects and disposal of used products. While the information and figures given here are typical of current production and conform to specification, minor variations may occur. No warranty expressed or implied is given concerning the accuracy of the information or the suitability of the products.